

Light Kit

Instructions









- **Faceplate Cover**
- Flagpole Bracket and Electrical
- 4) Bracket Insert for 4-5" diameter flag pole
- Photo-Electric Cell
- 6) Cable Clamp
- Wire Connectors 7)

Extend the end of the twisted wire beyond the end of the solid wire.



where indicated

Up turns On the LED Light Earlier in the evening

Down turns On the LED Light Later in the evening

Wrap a 24" length of

PVC tape around the threads. (8 revolutions)

The rubber washer can

be discarded.

Orient the shutter sideways to the LED Light Beam and away from the sun



- 1. Use minimum 14-2 UF-B/G wire protected by a 15A breaker to supply the Flag Pole Light.
- 2. The Electrical Box and the LED Light must be grounded through the UF-B wire for safety.
- 3. If the conduit is terminated end before burial to prevent ants from nesting in the Electrical Box.
- of the flag pole away from your neighbors.

If the Patriot Light turns itself off during the day, the sensor is working properly.

If after dark, the LED Light cycles on and off every few minutes, the sensor is being triggered by light from the LED Light and needs to be reoriented.

LED Light underground, seal the underground Bare/Gree 4. Orient the Electrical Box on the side 120V Recommended Gasket Turf Bury Caution Tape 1' above wire CAUTION CAUTION CAUTION CAUTION 2' Minimum 14-2 UF-B W/G Wire Weatherproof Silicon Sealant

Electrical

Box

The sensor has a built-in delay to minimize intermittent light triggers. When making sensor changes, allow a minute or two to verify your adjustment.